



- **Stainless Steel**
- **Wide Inner Race**
- **SR-type or L3-type Seals**
- **Set Screw Lock**

The **Sentinel** Line from **KBZ** offers a variety of Corrosion Resistant products including Stainless Steel, Nickel Plating and Thermo-Plastic Housings.

- **Balls & Rings**
- **Seal**
- **Slinger and Seal Frame**
- **Retainer**
- **Set Screws**
- **Lubrication**

- AISI 440 Stainless Steel**
- Silicone Rubber**
- AISI 302 Stainless Steel**
- AISI 304 Stainless Steel**
- AISI 420 Stainless Steel**
- H-1 Food Grade Grease**

Bearing No.	Bore Dia. Of Bearing		Dimensions (in.) (mm)							Basic Load Rating (lbs.)	Basic Static Load Rating (lbs.)	
	(in.)	(mm)	D	Bi	Be	N	M	G	DS(in.)			
SUC 201		12										
SUC 202		15										
SUC 202-10	5/8	17	1.575	1.079	0.591	0.5	0.721	0.197	1/4-28UNF	2,740	1,600	
SUC 203		17	40.0	27.4	15	12.7	18.3	5.0				
SUC 204		20	1.850	1.221	0.63	0.5	0.721	0.197	1/4-28UNF	2,740	1,600	
SUC 204-12	3/4	20	47.0	31.0	16.0	12.7	18.3	5.0				
SUC 205		25	2.048	1.343	0.669	0.563	0.776	0.217	1/4-28UNF	3,010	1,750	
SUC 205-16	1	25	52.0	34.1	17.0	14.3	19.7	5.5				
SUC 206		30	2.441	1.5	0.748	0.626	0.874	0.236	1/4-28UNF	4,200	2,430	
SUC 206-18	1 1/8	30	62.0	38.1	19.0	15.9	22.2	6.0				
SUC 206-19	1 3/16											
SUC 206-20	1 1/4											
SUC 207		35	2.835	1.689	0.787	0.689	1.0	0.256	5/16-24UNF	5,535	3,340	
SUC 207-20	1 1/4	35	72.0	42.9	20.0	17.5	25.4	6.5				
SUC 207-21	1 3/8											
SUC 207-22	1 7/16											
SUC 208		40	3.15	1.937	0.827	0.748	1.189	0.315	5/16-24UNF	6,375	3,960	
SUC 208-24	1 1/2	40	80.0	49.2	21.0	19.0	30.2	8.0				
SUC 209		45	3.347	1.937	0.866	0.748	1.189	0.315	5/16-24UNF	7,110	4,460	
SUC 209-28	1 3/4	45	85.0	49.2	22.0	19.0	30.2	8.0				
SUC 210		50	3.543	2.032	0.945	0.748	1.284	0.354	3/8-24UNF	7,400	4,910	
SUC 210-31	1 15/16	50	90.0	51.6	24.0	19.0	32.6	9.0				
SUC 210-32	2											
SUC 211		55	3.937	2.189	0.984	0.874	1.315	0.394	3/8-24UNF	-	-	
SUC 211-33	2 1/16	55	100	55.6	25	22.2	33.4	10				
SUC 211-34	2 1/8											
SUC 211-35	2 3/16											
SUC 212		60	4.331	2.563	1.063	1.00	1.563	0.394	3/8-24UNF	-	-	
SUC 212-36	2 1/4	60	110	65.1	27	25.4	39.7	10				
SUC 212-37	2 5/16											
SUC 212-38	2 3/8											