



- Set screw lock
- Narrow Inner Race
- A-type Seals
- Available in Relubricatable or Non-Relubricatable
- Spherical(SB) and Cylindrical(CSB) Outer Race

Unit No.	Bore Dia. Of Bearing		Dimensions (in.) (mm)							Basic Load Rating (kgs.)	Basic Static Load Rating (kgs.)	
	d		Be	D	Bi	N	M	G	Ds			
	(in.)	(mm)										
SB 201		12										
SB 201-8	1/2											
SB 202		15	0.472	1.575	0.866	0.236	0.63	0.177			960	480
SB 202-10	5/8		12.0	40.0	22.0	6.0	16.0	4.5	10-32UNF			
SB 203		17										
SB 204-12	3/4		0.551	1.85	0.984	0.276	0.709	0.177			1,280	750
SB 204		20	14.0	47.0	25.0	7.0	18.0	4.5	1/4-28UNF			
SB 205-14	7/8											
SB 205-15	15/16		0.591	2.047	1.063	0.295	0.768	0.197			1,400	790
SB 205		25	15.0	52.0	27.0	7.5	19.5	5	1/4-28UNF			
SB 205-16	1											
SB 206-17	1 1/16											
SB 206-18	1 1/8		0.623	2.441	1.181	0.315	0.866	0.217			1,950	1,130
SB 206		30	16.0	62.0	30.0	8.0	22.0	5.5	1/4-28UNF			
SB 206-19	1 3/16											
SB 206-20	1 1/4S											
SB 207-20	1 1/4											
SB 207-21	1 5/16		0.669	2.835	1.260	0.335	0.925	0.236			2,570	1,540
SB 207-22	1 3/8		17.0	72.0	32.0	8.5	23.5	6.0	5/16-24UNF			
SB 207		35										
SB 207-23	1 7/16											
SB 208-24	1 1/2		0.709	3.15	1.339	0.354	0.984	0.315			2,910	1,790
SB 208-25	1 9/16		18.0	80.0	34.0	9.0	25.0	8.0	5/16-24UNF			
SB 208		40										
SB 209		45										
SB 209-26	1 5/8		0.748	3.347	1.622	0.402	1.221	0.315			-	-
SB 209-27	1 11/16		19	85	41.2	10.2	31	8.0	5/16-24UNF			
SB 209-28	1 3/4											
SB 210		50										
SB 210-30	1 7/8		0.787	3.543	1.713	0.429	1.284	0.354			-	-
SB 210-31	1 15/16		20	90	43.5	10.9	32.6	9	5/16-24UNF			
SB 210-32	2											
SB 211		55										
SB 211-33	2 1/16		0.827	3.937	1.784	0.465	1.319	0.394			-	-
SB 211-34	2 1/8		21	100	45.3	11.8	33.5	10	3/8-24UNF			
SB 211-35	2 3/16											
SB 212		60										
SB 212-36	2 1/4		0.866	4.331	2.114	0.587	1.528	0.394			-	-
SB 212-37	2 5/16		22	110	53.7	14.9	38.8	10	3/8-24UNF			
SB 212-38	2 3/8											