



- Ductile Iron Housing
- Narrow Inner Race
- A-type Seal
- Eccentric Locking Collar

Unit No.	Shaft Dia.		Dimensions (in.) (mm)										Bolt Used	Bearing No.	
	d		A	E	L	G	S	B	Z	K	Bi	N			M
	(in.)	(mm)												(in.)	
SAFTD 201		12													SA 201
201-8	1/2														201-8
202		15	3.25	2.563	0.422	0.719	0.281	2.281	1.328	1.260	1.125	0.236	0.516	1/4	202 FTD 203
202-10	5/8									28.6	28.6	6.0	13.1		202-10
203		17													203
SAFTD 204-12	3/4													5/16	SA 204-12
204		20	3.688	2.813	0.438	0.766	0.344	2.609	1.438	1.311	1.221	0.276	0.571		204 FTD 204
SAFTD 205-14	7/8														SA 205-14
205-15	15/16														205-15
205		25	3.875	3	0.438	0.797	0.344	2.719	1.422	1.500	1.221	0.295	0.557	5/16	205 FTD 205
205-16	1									38.1	31	7.5	14		205-16
SAFTD 206-17	1 1/16														SA 206-17
206-18	1 1/8														206-18
206		30	4.563	3.531	0.5	0.859	0.406	3.203	1.641	1.752	1.406	0.315	0.622	3/8	206 FTD 206
206-19	1 3/16									44.5	35.7	8.0	15.8		206-19
206-20	1 1/4S														206-20
SAFTD 207-20	1 1/4														SA 207-20
207-21	1 5/16														207-21
207-22	1 3/8														207-22 FTD 207
207		35	4.813	3.938	0.5	0.938	0.406	3.516	1.797	2.189	1.532	0.335	0.665	3/8	207
207-23	1 7/16									55.6	38.9	8.5	16.9		207-23