



- Cast Iron Housing
- Narrow Inner Race
- A-type Seal
- Eccentric Locking Collar

Unit No.	Shaft Dia.		Dimensions (in.)											Bolt Used	Bearing No.	Housing No.	
	d		A	E	I	G	L	S	B	Z	K	Bi	N				M
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)		
SALF 201		12														SA 201	
201-8	1/2	12	3.188	2.5	0.394	0.394	0.719	0.279	2.205	1.284	1.260	1.125	0.236	0.516	1/4	201-8	
202		15	81	63.5	10	10	18	7.1	56	32.6	28.6	28.6	6.0	13.1		202	LF 203
202-10	5/8	15														202-10	
203		17														203	
SALF 204-12	3/4	20	3.531	2.813	0.438	0.438	0.781	0.354	2.406	1.378	1.311	1.221	0.276	0.571	5/16	SA 204-12	LF 204
204		20	90	71.5	11	11	20	9	61	35	33.3	31	7.0	14.5		204	
SALF 205-14	7/8	25	3.75	2.984	0.438	0.438	0.781	0.374	2.513	1.358	1.500	1.221	0.295	0.557	5/16	SA 205-14	
205-15	15/16	25	95	76	11	11	20	9.5	64	34.5	38.1	31	7.5	14		205-15	LF 205
205		25														205	
205-16	1	25														205-16	
SALF 206-17	1 1/16	30	4.438	3.563	0.469	0.469	0.906	0.433	3	1.563	1.752	1.406	0.315	0.622	3/8	SA 206-17	
206-18	1 1/8	30	113	90.5	12	12	23	11	76	39.7	44.5	35.7	8.0	15.8		206-18	LF 206
206		30														206	
206-19	1 3/16	30														206-19	
206-20	1 1/4S	30														206-20	
SALF 207-20	1 1/4	35	4.813	3.938	0.516	0.5	0.938	0.433	3.5	1.709	2.189	1.532	0.335	0.665	3/8	SA 207-20	
207-21	1 5/16	35	122	100	13	13	24	11	89	43.4	55.6	38.9	8.5	16.9		207-21	LF 207
207-22	1 3/8	35														207-22	
207		35														207	
207-23	1 7/16	35														207-23	