



- Cast Iron Housing
- Eccentric Locking Collar
- Wide Inner Race
- SR-type or L3-type Seals

Unit No.	Shaft Dia.		Dimensions (in.)										Bolt Used	Bearing No.	Housing No.		
	<i>d</i>	<i>d</i>	A	E	I	G	L	S	B	Z	K	Bi				N	M
	(in.)	(mm)	(in.)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(in.)			
NANFL 201																NA 201	
201-8	1/2	4.449	3.531	0.75	0.438	1.161	0.391	2.362	1.791	1.311	1.713	0.669	0.669	5/16	201-8		
202		113	89.7	19	11	29.5	10	60	45.5	33.3	43.5	17	17		202	NFL 203	
202-10	5/8														202-10		
203															203		
NANFL 204-12	3/4	4.449	3.531	0.75	0.438	1.161	0.391	2.362	1.791	1.311	1.713	0.669	0.669	5/16	NA 204-12		
204		113	89.7	19	11	29.5	10	60	45.5	33.3	43.5	17	17		204	NFL 204	
NANFL 205-14	7/8														NA 205-14		
205-15	15/16	5.118	3.891	0.719	0.5	1.22	0.469	2.677	1.839	1.500	1.744	0.685	0.685	3/8	205-15		
205		130	99	20	13	31	12	68	46.7	38.1	44.3	17.4	17.4		205	NFL 205	
205-16	1														205-16		
NANFL 206-17	1 1/16														NA 206-17		
206-18	1 1/8	5.827	4.594	0.828	0.5	1.339	0.469	3.150	2.012	1.752	1.902	0.717	0.717	3/8	206-18		
206		148	117	21	13	34	12	80	51.1	44.5	48.3	18.2	18.2		206	NFL 206	
206-19	1 3/16														206-19		
206-20	1 1/4S														206-20		
NANFL 207-20	1 1/4														NA 207-20		
207-21	1 5/16	6.339	5.125	0.844	0.563	1.437	0.516	3.531	2.118	2.189	2.012	0.74	0.74	7/16	207-21		
207-22	1 3/8	161	130	21.5	14	36.5	13	89.7	53.8	55.6	51.1	18.8	18.8		207-22	NFL 207	
207															207		
207-23	1 7/16														207-23		
NANFL 208-24	1 1/2	6.890	5.656	0.938	0.563	1.535	0.516	3.938	2.319	2.374	2.217	0.843	0.843	7/16	NA 208-24		
208-25	1 9/16	175	144	24	14	39	13	100	58.9	60.3	56.3	21.4	21.4		208-25	NFL 208	
208															208		
NANFL 209	45														NA 209		
209-26	1 5/8	7.402	5.844	0.938	0.594	1.575	0.594	4.25	2.319	2.50	2.217	0.843	0.843	1/2	209-26		
209-27	1 11/16	188	148	24	14	40	15	108	58.9	63.5	56.3	21.4	21.4		209-27	NFL 209	
209-28	1 3/4														209-28		
NANFL 210	50														NA 210		
210-30	1 7/8	7.756	6.188	1.125	0.594	1.831	0.594	4.531	2.622	2.752	2.469	0.969	0.969	1/2	210-30		
210-31	1 15/16	197	157	28.5	14	46.5	15	115.1	66.6	69.9	62.7	24.6	24.6		210-31	NFL 210	
210-32	2														210-32		
NANFL 211	55														NA 211		
211-32	2	8.819	7.244	1.266	0.719	1.969	0.650	5.125	2.98	3	2.811	1.091	1.091	9/16	211-32		
211-34	2 1/8	224	184	32	20	50	16.5	130.2	75.7	76.2	71.4	27.7	27.7		211-34	NFL 211	
211-35	2 3/16														211-35		