



- Cast Iron Housing
- Narrow Inner Race
- A-type Seal
- Eccentric Locking Collar

Unit No.	Shaft Dia.		Dimensions (in.)											Bolt Used	Bearing No.	Housing No.
	d		(mm)													
	(in.)	A	E	i	G	I	S	B	Z	K	Bi	N	M	(in.)		
SAFL 201																
201-8	1/2	3.898	3	0.591	0.438	1.004	0.365	2.219	1.234	1.260	1.125	0.236	0.516	3/8	SA 201	
202		99	76.2	15	11	25.5	9	56.4	31	28.6	28.6	6.0	13.1		201-8	
202-10	5/8														202	FL 203
203															202-10	
SAFL 204-12	3/4	4.438	3.531	0.591	0.438	1.004	0.391	2.375	1.266	1.311	1.221	0.276	0.571	3/8	SA 204-12	
204		113	90	15	11	25.5	10	60.3	32.1	33.3	31	7.0	14.5		204	FL 204
SAFL 205-14	7/8														SA 205-14	
205-15	15/16	5.125	3.891	0.629	0.5	1.063	0.469	2.688	1.391	1.500	1.221	0.295	0.557	3/8	205-15	
205		130	99	16	13	27	12	68.3	35	38.1	31	7.5	14		205	FL 205
205-16	1														205-16	
SAFL 206-17	1 1/16														SA 206-17	
206-18	1 1/8	5.813	4.594	0.709	0.5	1.219	0.469	3.156	1.578	1.752	1.406	0.315	0.622	1/2	206-18	
206		148	117	18	13	31	12	80.2	40	44.5	35.7	8.0	15.8		206	FL 206
206-19	1 3/16														206-19	
206-20	1 1/4S														206-20	
SAFL 207-20	1 1/4														SA 207-20	
207-21	1 5/16														207-21	
207-22	1 3/8	6.344	5.125	0.748	0.591	1.344	0.516	3.531	1.672	2.189	1.532	0.335	0.665	1/2	207-22	
207		161	130	19	15	34	13	89.7	42	55.6	38.9	8.5	16.9		207	FL 207
207-23	1 7/16														207-23	
SAFL 208-24	1 1/2														SA 208-24	
208-25	1 9/16	6.875	5.656	0.827	0.591	1.406	0.516	3.938	1.813	2.374	1.721	0.354	0.835	1/2	208-25	
208		175	144	21	15	36	13	100	46	60.3	43.7	9.0	21.2		208	FL 208
SAFL 209	45MM														SA 209	
209-26	1 5/8	7.406	5.844	0.866	0.629	1.5	0.594	4.25	2.063	2.5	1.721	0.374	0.815	1/2	209-26	
209-27	1 11/16	188	148	22	16	38	15	108	52	63.5	43.7	9.5	20.7		209-27	
209-28	1 3/4														209-28	
SAFL 210	50MM														SA 210	
210-30	1 7/8	7.75	6.188	0.866	0.629	1.563	0.594	4.531	2.156	2.752	1.721	0.397	0.795	5/8	210-30	
210-31	1 15/16	197	157	22	16	40	15	115.1	55	69.9	43.7	10	20.2		210-31	
210-32	2														210-32	
SAFL 211	55MM														SA 211	
211-32	2	8.813	7.244	0.984	0.709	1.688	0.641	5.125	2.313	3	1.906	0.413	0.868	5/8	211-32	
211-34	2 1/8	224	184	25	18	43	16	130.2	59	76.2	48.4	10.5	22		211-34	
211-35	2 3/16														211-35	FL 211