



- Cast Iron Housing
- Eccentric Locking Collar
- Wide Inner Race Bearing
- SR-type or L3-type Seals
- Relubricateable

Unit No.	Shaft Dia.		Dimensions (in.)											Bolt Used	Bearing No.	Housing No.	
	d		(mm)														
	(in.)	(mm)	A	E	I	G	L	S	Z	Bi	N	M	J	K	(in.)		
NANF 201		12														NA 201	
201-8	1/2	15	3.375	2.125	0.75	0.594	1.156	0.438	1.781	1.713	0.669	0.669	0.374	1.311	3/8	201-8	
202		15	86	54	19	15	29.5	11	45.5	43.5	17.0	17.0	9.5	33.3		202	NF 203
202-10	5/8	17														202-10	
203		17														203	
NANF 204-12	3/4	20	3.375	2.5	0.75	0.594	1.156	0.438	1.781	1.713	0.669	0.669	0.374	1.311	3/8	NA 204-12	NF 204
204		20	86	64	19	15	29.5	11	45.5	43.5	17.0	17.0	9.5	33.3		204	
NANF 205-14	7/8	25	3.75	2.75	0.781	0.594	1.219	0.453	1.844	1.744	0.685	0.685	0.374	1.5	3/8	NA 205-14	
205-15	15/16	25	95	70	20	15	31	11.5	46.9	44.3	17.4	17.4	9.5	38.1		205-15	
205		25														205	NF 205
205-16	1	25														205-16	
NANF 206-17	1 1/16	30	4.25	3.25	0.828	0.625	1.969	0.516	2	1.902	0.717	0.717	0.469	1.752	7/16	NA 206-17	
206-18	1 1/8	30	108	83	21	16	34	13	51.1	48.3	18.2	18.2	11.9	44.5		206-18	NF 206
206		30														206	
206-19	1 3/16	30														206-19	
206-20	1 1/4S	30														206-20	
NANF 207-20	1 1/4	35	4.594	3.625	0.844	0.656	1.438	0.516	1.125	2.012	0.74	0.74	0.532	2.189	7/16	NA 207-20	
207-21	1 5/16	35	117	92	21.5	17	36.5	13	53.8	51.1	18.8	18.8	13.5	55.6		207-21	NF 207
207-22	1 3/8	35														207-22	
207		35														207	
207-23	1 7/16	35														207-23	
NANF 208-24	1 1/2	40	5.125	4	0.938	0.656	1.531	0.547	2.313	2.217	0.843	0.843	0.532	2.374	1/2	NA 208-24	
208-25	1 9/16	40	130	102	24	17	39	14	58.9	56.3	21.4	21.4	13.5	60.3		208-25	NF 208
208		40														208	
NANF 209-26	1 5/8	45	5.406	4.125	0.938	0.719	1.563	0.625	2.313	2.217	0.843	0.843	0.532	2.5	9/16	NA 209-26	
209-27	1 11/16	45	137	105	24	18	40	16	58.9	56.3	21.4	21.4	13.5	63.5		209-27	NF 209
209-28	1 3/4	45														209-28	
209		45														209	
NANF 210-30	1 7/8	50	5.625	4.375	1.125	0.781	1.844	0.625	2.625	2.469	0.969	0.969	0.532	2.752	9/16	NA 210-30	
210-31	1 15/16	50	143	111	28.5	20	46.5	16	66.6	62.7	24.6	24.6	13.5	69.9		210-31	NF 210
210		50														210	
210-32	2S	50														210-32	
NANF 211-32	2	55	6.375	5.125	1.266	0.813	1.969	0.672	2.969	2.811	1.091	1.091	0.63	3.0	5/8	NA 211-30	
211-34	2 1/8	55	162	130	32	21	50	17	75.7	71.4	27.7	27.7	16.0	76.2		211-31	NF 211
211		55														211	
211-35	2 3/16	55														211-32	
NANF 212-36	2 1/4	60	6.875	5.625	1.422	0.813	2.156	0.672	3.25	3.063	1.217	1.217	0.63	3.315	5/8	NA 212-36	
212		60	175	143	36	21	55	17	82.9	77.8	30.9	30.9	16.0	84.2		212	NF 212
212-38	2 3/8	60														212-38	
212-39	2 3/16	60														212-39	