



- Cast Iron Housing
- Wide Inner Race
- SR-type or L3-type Seals
- Lower Shaft Height
- Eccentric Locking Collar

Unit No.	Shaft Dia.		Dimensions (in.) (mm)												Bolt Used (in.)	Bearing Housing No.	Housing No.		
	(in.)	(mm)	H	A	E	B	S2	S1	G	W	Bi	N	M	J				K	
NAPL 201		12																NA 201	
201-8	1/2	15	1.25	5.236	3.858	1.614	0.629	0.512	0.563	2.48	1.713	0.669	0.669	0.374	1.311	3/8	NA 201-8		
202		15	31.8	133	98	41	16	13	14	63	43.5	17	17	9.5	33.3		202	PL 203	
202-10	5/8	17															202-10		
203		17															203		
NAPL 204-12	3/4	20	1.25	5.236	3.858	1.614	0.629	0.512	0.563	2.48	1.713	0.669	0.669	0.374	1.311	3/8	NA 204-12	PL 204	
204		20	31.8	133	98	41	16	13	14	63	43.5	17	17	9.5	33.3		204		
NAPL 205-14	7/8																NA 205-14		
205-15	15/16	25	1.313	5.5	4.125	1.732	0.629	0.512	0.625	2.677	1.744	0.685	0.685	0.374	1.5	3/8	205-15		
205		25	33.3	140	105	44	16	13	16	68	44.3	17.4	17.4	9.5	38.1		205	PL 205	
205-16	1																205-16		
NAPL 206-17	1 1/16																NA 206-17		
206-18	1 1/8	30	1.563	6.299	4.75	1.889	0.748	0.591	0.669	3.156	1.902	0.717	0.717	0.469	1.752	1/2	206-18	PL 206	
206		30	39.7	160	121	48	19	15	17	80	48.3	18.2	18.2	11.9	44.5		206		
206-19	1 3/16																206-19		
206-20	1 1/4S																206-20		
NAPL 207-20	1 1/4																NA 207-20		
207-21	1 5/16	35	1.813	6.594	5	1.889	0.748	0.591	0.748	3.622	2.012	0.74	0.74	0.532	2.189	1/2	207-21	PL 207	
207-22	1 3/8		46	167	127	48	19	15	19	92	51.1	18.8	18.8	13.5	55.6		207-22		
207		35															207		
207-23	1 7/16																207-23		
NAPL 208-24	1 1/2																NA 208-24		
208-25	1 9/16	40	1.938	7.125	5.512	2.125	0.748	0.591	0.748	3.937	2.217	0.843	0.843	0.532	2.374	1/2	208-25	PL 208	
208		40	49.2	181	140	54	19	15	19	100	56.3	21.4	21.4	13.5	60.3		208		
NAPL 209-26	1 5/8																NA 209-26		
209-27	1 11/16	45	2.063	7.48	5.75	2.125	0.748	0.591	0.827	4.173	2.217	0.843	0.843	0.532	2.5	1/2	209-27	PL 209	
209-28	1 3/4		52.4	190	146	54	19	15	21	106	56.3	21.4	21.4	13.5	63.5		209-28		
209		45															209		
NAPL 210-30	1 7/8																NA 210-30		
210-31	1 15/16	50	2.188	7.99	6.25	2.25	0.748	0.591	0.866	4.453	2.032	0.969	0.969	0.532	2.752	5/8	210-31	PL 210	
210		50	55.6	203	159	57	19	15	22	113	51.6	24.6	24.6	13.5	69.9		210		
210-32	2S																210-32		
NAPL 211-32	2																NA 211-30		
211-34	2 1/8	55	2.438	9.134	7.126	2.375	0.945	0.787	0.984	4.921	2.189	1.091	1.091	0.63	3.0	5/8	211-31	PL 211	
211		55	61.9	232	181	60	24	20	25	125	55.6	27.7	27.7	16.0	76.2		211		
211-35	2 3/16																211-32		
NAPL 212-36	2 1/4																NA 212-36		
212		60	2.688	9.488	7.5	2.519	0.945	0.787	1.142	5.354	2.56	1.217	1.217	0.63	3.315	5/8	212	PL 212	
212-38	2 3/8		68.3	241	190.5	64	24	20	29	136	65.1	30.9	30.9	16.0	84.2		212-38		
212-39	2 7/16																212-39		
NAPL 213-40	2 1/2																NA 213-40	PL 213	
213		65	2.688	9.75	7.625	2.75	1.142	0.787	1.063	5.551	2.563	1.343	1.343	0.689	3.386	5/8	213		
		65	68.3	248	194	70	29	20	27	141	65.1	34.1	34.1	17.5	86.0				
NAPL 215-47	2 15/16																NA 215-47		
215		75	3.311	11.969	9.488	2.913	1.259	0.866	1.259	6.496	3.063	1.469	1.469	0.689	4.016	7/8	215	PL 215	
215-48	3		84.1	304	241	74	32	22	32	165	77.8	37.3	37.3	17.5	102.0		215-48		