



PTEF Liners Available

MPI Part No	Dimensions [in.]							a° Mis. Angle	Radial Static Load Cap.	Approx Weight
	d	D	W	T	d ₁	d ₂	F Chamfer			
						<i>ref</i>	<i>ref</i>	<i>ref</i>	<i>lbs.</i>	<i>lbs.</i>
COM-3	3/16	.5625	.281	.218	.293	.406	.015	11	3,250	.014
COM-4	1/4	.6562	.343	.250	.364	.500	.022	13.5	4,925	.022
COM-5	5/16	.7500	.375	.281	.419	.562	.032	12	6,475	.030
COM-6	3/8	.8125	.406	.312	.516	.656	.032	10	8,400	.038
COM-7	7/16	.9062	.437	.343	.530	.687	.032	8	9,455	.047
COM-8	1/2	1.000	.500	.390	.600	.781	.032	9.5	13,250	.065
COM-9	9/16	1.0937	.562	.437	.671	.875	.032	9.5	16,625	.085
COM-10	5/8	1.1875	.625	.500	.739	.968	.032	8.5	21,275	.110
COM-12	3/4	1.4375	.750	.593	.920	1.187	.044	9	31,920	.204
COM-14	7/8	1.5625	.875	.703	.978	1.312	.044	9.5	41,950	.263
COM-16	1	1.7500	1.000	.797	1.118	1.500	.044	10	55,200	.388

- Larger sizes available. To request data, use the [Contact Us](#) button or call 1/800/695-6767
- Lubrication groove & hole in outer race
- For PTFE liner add 'T' to the end. (COM-8T)

Material

Ball	Race
52100 Chromium Steel Heat Treated w/ Hard Chrome Plating	Low Carbon Steel w/ Oil coat